

SIDEWALKS (CS) SPECIAL PROVISIONS

In addition to the attached General Provisions (TR-0045), the following special provisions are applicable:

1. A State issued permit is required for any landscaping or tree installation, including installation of tree wells.
2. A separate permit must be obtained from Caltrans for any driveway, handicap-ramp installations or any sidewalks that are other than Portland Cement Concrete constructed in compliance with Caltrans Standard Specifications.
3. Traffic control is authorized only between 9 am and 3 p.m., Monday through Friday, holidays excluded. Any traffic control that requires lane closure shall be in compliance with the appropriate traffic control plan. Where required by the plan, the use of a flashing arrowboard is MANDATORY.
4. New curb and gutter installations shall be State Standard Type A2-6, unless necessary to conform to existing adjacent curb and gutter installations.
5. Normally, the back edge of a sidewalk shall be placed on the right of way line. Sidewalk width shall be minimum of 5' (1.5 m).
6. Alignment and grade of gutter and sidewalk shall match the existing.
7. Existing concrete curb and paved shoulder shall be saw cut to a neat line prior to excavating and forming. Existing concrete sidewalk shall be saw cut at the scoreline. Paved shoulder shall be replaced with asphalt concrete paving material equal "in kind" and thickness to existing shoulder and shall conform to lip of new curb and gutter.
8. Permittee shall be responsible for the relocation or adjustment of any utility required as the result of work authorized by this permit, and utility relocation shall be completed prior to the installation of any new curb, gutter or sidewalk.
9. A monolithic pour of sidewalk and curb and gutter shall not be permitted.